



מארז כונן ודיסק WINSTARS WSUEC320A ומשכפל דיסקים

מק"ט: HDD-DOCK

₪359 ~~₪459~~

משכפל מדיסק לדיסק -גם ללא מחשב

כולל מפצל USB

תחנת עגינה ל 2 דיסקים במקביל (2.5 או 3.5)

כפתור גיבוי

קורא כרטיסים

תיאור מוצר

משכפל מדיסק לדיסק -גם ללא מחשב

תחנת עגינה ל 2 דיסקים במקביל (2.5 או 3.5)

כפתור גיבוי

קורא כרטיסים

כולל מפצל USB

Communicator D2 Combo is a multi purpose storage device which including HDD/ Flash Disk or Wireless optional input for data storage. Application for system backup / video editing / enlarge drive capacity from two different size HDD appear to one drive. Create diverse value-added applications besides flash card reader such as E-commerce, phone book/ SMS edit/ save/ backup for mobile SIM cards through the smart card interface. Convenience communication through Bluetooth /WiFi for data transfer from Communicator D2 Combo to other devices such as ...Mobile phone/ MP3 etc

Overall Descriptions

eSATA or USB host to Dual 2.5"/ 3.5" SATA drive

-Running on eSATA to SATA HDD and fulfill USB Input function simultaneously

-1.5Gpbs or 3Gpbs link rate with auto-negotiation

-Enhanced 2nd Generation **PICO 1.9 SteelVine Storage Processor**. PICO is a simple RISC based embedded Central Processing Unit that reduced Instruction set from Computer system that be improve the performance of the whole System

-Virtualized multiple storage devices into one or many units, **Mutli-Drive spanning, Drive partition or act as a JBOD Port Multiplier**

-Host side NCQ support over SATA, adding with FIFO per devices for reads and writes

-Hot Plug support

-Compliant with USB 2.0 Specifications

-Full and High-G-tech rates (12~480Mb/s) USB operation

-Support for Drive Locking using ATA proprietary commands

-OTG backup program with Backup Button

-LED indicate with Storage Device

-**SteelVine Manager Software Tools** enable you to configured setup with eSATA or USB host connections from your PC to the Communicator D2 Combo

Flash Media Card Reader

- High-speed USB 2.0 interface; backward compatible with USB 1.1
- Supports multiple flash card interfaces and the latest flash card specifications
- SD/MMC, MS/MSPro, SM/xD and MicroSD/MMC Micro. (SD/MMC bus interface for dedicated MicroSD™/MMC Micro™/T-Flash™ slot)
- Supports SIM port** to enable Subscriber Identity Module Card phone book/SMS managements

Enhanced NEC powered USB2.0 Vertical Port

- Compliant with Universal Serial Bus Specification Revision 2.0
- Certified by USB Implementers forum and granted the USB 2.0 High-G-tech Logo
- Supports Over-current detection** and individual or ganged power control
- Provide wide insertion space for large USB device

Optional

- External DVI VGA Adapter** enable you extend your PC system link up to 6 display units for Mirror or Extended Display, resolution up to 1600x1280 at 32 bit true color, Satisfy extended viewing purpose or multi-tasking need
- 2.4GHz 802.11g WiFi or Bluetooth** both are convenience for wireless communication or data transfer to other devices
- Additional USB2.0 Port** more USB connectivity able

Features

- eSATA or USB 2.0 host to dual 2.5"/3.5" SATA drive .1
- 2. Flash Media Card Reader (SD+MS/ M2+SM/ XD Sim Card)
- 3. Enhanced NEC powered USB2.0 Vertical Port x 2

Optional package I

- 1. 2.4GHz 802.11g WiFi or BlueTooth
- 2. Enhanced USB2.0 Port x 1

Optional package II

- 1. External DVI VGA Adapter
- 2. 2.4GHz 802.11g WiFi or BlueTooth
- 3. Enhanced USB2.0 Port x 1

Specifications

Requirements

PC Systems

1. Intel Pentium-III 500MHz equivalent or faster
2. CD-ROM Drive
3. 64MB Memory (Minimum)
4. 250MB of free disk space
5. Super VGA (800x600) or higher resolution display with at least 256 colors
6. Mouse or compatible pointing device
7. Windows 2000/XP/2003 Server or Windows Vista with the latest Service Packs
8. SATA connection: Communicator D2 Combo and associated software drivers, or any other third-party SATA host controller with Port Multiplier support
9. USB connection: USB 1.0 or 2.0 direct host connection or USB hub

Macintosh Systems

1. PowerMac G5, MacBook Pro or Mac Pro
2. CD-ROM Drive
3. Mouse or compatible pointing device
4. MacOS X, 10.4.8 (or later)
5. SATA connection: Communicator D2 Combo and associated software drivers, or any other third-party SATA host controller with Port Multiplier support
6. USB connection: USB 1.0 or 2.0 direct host connection or USB hub

Package Content

Communicator D2 Combo Docking Station

Power Adapter 12V / 5A with Power Cable

SATA Cable: eSATA to eSATA Cable

USB Cable

User Manual

CD Software Tools